



ADHESIVES, SEALANTS, GREASES & SPECIAL PRODUCTS



SEALANTS AND PRIMERS



Code	Description	Size	Colour
MM SIK 290DC	Sikaflex Sealant 290DC	310ml	Black
MM SIK 290DC600	Sikaflex Sealant 290DC	600ml	Black
MM SIK 291IW	Sikaflex Sealant 291i	310ml	White
MM SIK 291IB	Sikaflex Sealant 291i	310ml	Black
MM SIK 291IW100	Sikaflex Sealant 291i	310ml	White
MM SIK 291IB100	Sikaflex Sealant 291i	310ml	Black
MM SIK 292i	Sikaflex Sealant 292i	310ml	White
MM SIK 295UVW	Sikaflex Sealant 295UV	310ml	White
MM SIK 295UVB	Sikaflex Sealant 295UV	310ml	Black
MM SIK 298600	Sikaflex Sealant 298	600ml	Black
MM SIK 521UVW	Sikaflex Sealant 521UV	310ml	White
MM SIK 521UVB	Sikaflex Sealant 521UV	310ml	Black
MM SIK 8561	Sikaflex Firestop Marine	310ml	Black
MM SIK 205	Sikaflex Cleaner 205 Multipurpose Activator/Cleaner	250ml/1lt	Clear
MM SIK 206	Sikaflex Primer 206G+P	250ml/1lt	Black
MM SIK 215	Sikaflex Primer 215	250ml/1lt	Clear
MM SIK MULTI	Sikaflex MultiPrimer Marine	250ml/1lt	Clear

SIKAFLEX GUIDELINE

- Sikaflex-291i Multi purpose marine sealant for interior and exterior applications with wide adhesion range
- Sikaflex-292i Structural adhesive for various bonding applications
- Sikaflex-295i UV The weathering resistant marine adhesive for sealing and bonding of organic glasses
- Sikaflex-298i Bedding compound
- Sikaflex-290i DC Weathering resistant and sandable deck caulking compound



CAULK AWAY



- Remove caulking with ease, get caulk out of those hard to reach corners.
- No scratching.
- No chemicals.
- Reusable and suitable for silicone, latex and acrylic.

Code: MM STB 92401

EPOXY PUTTY STICK



- Makes permanent and emergency repairs on fiberglass, wood, metal and plastic.
- Easy to use; just hand knead until color turns white and apply to damaged area.

4 oz. blister packs

Code: MM STB 87104

EPOXY GLUE



- Convenient self-metering syringe applicator
- Bonds fiberglass, rubber, hard plastic, glass, fabric, ceramic, and metal.
- Fills cracks and holes, mounts components, seals seams.
- Resists most liquids.
- Crystal clear appearance after curing.
- Permanent strength up to 3400 PSI.

1 oz. (28.3 g)

Code: MM STB 93401

CAULK RITE



- Great for applying a perfect bead of caulking.
- Great for applying grout between tiles.
- No mess.
- No edge marks.
- No waste.
- Suitable for all types of sealant and caulking.
- Easy to clean.

Code: MM STB 92501

EPOXY ALUMINIUM PUTTY STICK



- Makes permanent and emergency repairs on aluminum boats, outdrives, fuel and water tanks and other aluminum parts.
- Easy to use; just hand knead for 1 minute and apply to damaged area.

4 oz. blister packs

Code: MM STB 87004

SUPER GLUE GEL



- Creates ultra-high strength bonds.
- Gel formula keeps glue in place while curing occurs.
- Bonds in 15-30 seconds.
- Use to bond plastics, vinyl, textiles, leather, wood and ceramics.

0.07 oz. (2 g)

Code: MM STB 93501

**See complete STARBRITE product range
in section 27**

CLEAR MUSEUM GEL



Clear Museum Gel is a see-through product that protects glassware and crystal from toppling over and shattering. It's the professional collector's choice. Clear gel is designed primarily for glass-on-glass applications, although it can be used on most surfaces.

It's easy to use, just scoop a little out of the jar and roll it into balls. Place on the bottom of an object, press down lightly and twist into position. The gel gradually flows across the base of an item until it creates a superior invisible bond. The gel is designed for use on flat, level surfaces only and takes up to an hour to set properly. A 4 oz / 110 ml jar will secure an amazing 300 items!

Code: MM TRV MUSEUM110

3M

ADHESIVE AND SILICONE SEALANTS



Code	Description	Size	Colour
MM 3M 05205	3M Marine Adhesive Sealant 5200	3 oz Tube	Black
MM 3M 05203	3M Marine Adhesive Sealant 5200	3 oz Tube	White
MM 3M 06504	3M Marine Adhesive Sealant 5200	280 ml cartridge	Black
MM 3M 06500	3M Marine Adhesive Sealant 5200	280 ml cartridge	White
MM 3M 05601E	3M Silicone Sealant 3200	280 ml cartridge	Black
MM 3M 05600E	3M Silicone Sealant 3200	280 ml cartridge	White
MM 3M 05602E	3M Silicone Sealant 3200	280 ml cartridge	Clear

3M

CAULKING GUN



Code	Description
MM 3M 08013	3M Professional Pneumatic Caulking Gun

GLUES



Code	Description	Size
MM 3M SG10	3M Universal Contact Adhesive SG10	1 lt
MM 3M DP100	3M DP100 Fast Cure Epoxy Glue	50 ml

3M

TAPES



Code	Description	Size	Colour
MM 3M 3903	3M 3903 Vinyl Duct Tape	2"x50 MT	Grey
MM 3M 39031	3M 39031 Vinyl Duct Tape	2"x50 MT	Black

3M

3M ADHESIVE CLEANER



1 lt tin
Code: MM 3M 08984

GOO GONE



US #1 Brand for Sticky, Gummy, Greasy, Goopy Problems! Goo Gone's citrus power and scientific technology combine to defeat the toughest stains. Goo Gone can be used on hard surfaces, carpeting, upholstery, clothing, and more. Do not use on silk, leather, suede or rubber

3 oz bottle
Code: MM GOOGONE

See complete 3M product range in section 27

HENKEL TANGIT PVC-U GLUE



Special adhesive for bonding PVC-U pressure pipes as well as cables and sewage pipes and gutters.

- Long open time of 4 minutes
- Excellent gap-bridging capability
- Maximum leak protection

Temperature range
0°C to + 60°C.

Code	Size	Container
MM BNZ TG125	125 Gr	Tube
MM BNZ TG250	250 Gr	Tin
MM BNZ TG500	500 Gr	Tin
MM BNZ TG1	1 Kg	Tin

Full PVC fittings selection in section 15



SHELL GADUS GREASE



Code	Product	Features	Technology (Thickener, base oil and key properties)	ISO viscosity grade	NLGI grade	Specifications and approvals
MM SHE GADS5T100	Gadus S5 T100	• Long life • Extreme temperature • Polyurea	Polyurea, synthetic	100	2	Approved: AUMA Riester Listings: perma Schmiersysteme and Wood Group
MM SHE GADS5V100	Gadus S5 V100	• Long life • Improved efficiency • Lithium complex	Lithium complex, synthetic	100	2	Approved: Vestas Wind Systems Listings: ABB, CH Schäfer Getriebe, FLSmidth, Hegenscheidt-MFD and perma Schmiersysteme
MM SHE GADS3V460D	Gadus S3 V460D	• Heavy-duty protection • High temperature • Lithium complex	Lithium complex, mineral, EP, solid EP additive (MoS ₂)	460	2	Specification: Meets Caterpillar, Liebherr and P&H Mining Equipment Approved: Bucyrus International, CMI FPE Ltd, Gebr. Pfeiffer perma Schmiersysteme, Rothe Erde, SMS Meer and Voith Listings: BE (certified), Bucyrus International, CMI Groupe, Dieffenbacher, Gebr. Pfeiffer, Hitachi, Konecranes and Komatsu Mining
MM SHE GADS3V220C	Gadus S3 V220C	• Extra protection • High temperature • Red lithium complex	Lithium complex, mineral, EP	220	1, 2	Specification: Meets ASTM D4950-08 GC-LB. Approved: Aichelin, Dexter Axle, Sør-Norge Aluminium and Willy Vogel Listings: Listed by over 20 major companies from a wide variety of industries.
MM SHE GADS2V220	Gadus S2 V220	• Reliable protection • Multipurpose • Lithium	Lithium, mineral, EP	220	00, 0, 1, 2, 3	Specification: Meets ASTM D4950-08 LB Approved: Approved by 24 major companies from a wide variety of industries. Listings: Listed by over 100 companies from a wide variety of industries.
MM SHE GADS2V220AD	Gadus S2 V220AD	• Heavy-duty protection • Water resistant • Lithium calcium	Lithium calcium, mineral, EP, solid EP additive (MoS ₂)	220	1, 2	Approved: Sandvik (endorsed) and Xiamen XGMA Machinery Listings: Listed by 12 major companies from a wide variety of industries.
MM SHE GADS2V220AC	Gadus S2 V220AC	• Heavy-duty protection • Water resistant • Red lithium calcium	Lithium calcium, mineral, soluble EP additive	220	0, 1, 1.5, 2, 3	Approved: Willy Vogel Specification: Meets ASTM D4950-08 LB Listings: David Brown, Danieli, Eirich, Harburg-Freudenberger Maschinenbau, Maschinenfabrik Gustav Eirich, New Zealand Steel, Ondrives, Power Jacks Group, Tetra Pak International, ZZ-Antriebe
MM SHE GADS2V100	Gadus S2 V100	• Reliable protection • Multipurpose • Lithium	Lithium calcium, mineral, soluble EP additive	100	1, 2, 3	Approved: Approved by 18 major companies from a wide variety of industries. Listings: Listed by over 60 major companies from a wide variety of industries.



SKF BEARING GREASE LGGB2



LGGB 2 is a biodegradable, low toxicity grease, synthetic ester oil based using a lithium-calcium thickener. It has excellent lubrication properties for a wide range of applications operating under different conditions. This grease offers:

- Compliance with current regulations on toxicity and biodegradability
- Good performance in applications with steel-on-steel spherical plain bearings, ball bearings and roller bearings
- Good low temperature start-up performance
- Good corrosion inhibiting properties
- **Suitable for medium to high loads**

Code	Description	Size
MM SKF LGGB2/04	SKF LGGB 2/0.4 LGGB 2 Grease	420ml Cartridge



GREASES

	Code	Description	Size
	MM CFG L00300	White Lithium Grease	125 ml
	MM CFG L00302		500 ml
	MM CFG L00303		1000 ml
	MM CFG L00304		5000 ml
	MM CFG L00600	High Performance Grease	125 ml
	MM CFG L00602		500 ml
	MM CFG L00603		1000 ml
	MM CFG L00604		5000 ml
	MM CFG L00100	Tech Vaseline Grease	125 ml
	MM CFG L00101		500 ml
	MM CFG L00103		1000 ml
	MM CFG L00104		5000 ml
	MM CFG L00400	Molibdene Bisulphure Grease	125 ml
	MM CFG L00402		500 ml
	MM CFG L00403		1000 ml
	MM CFG L00404		5000 ml
	MM CFG L01400	White Teflub Grease PTFE	125 ml
	MM CFG L01401		500 ml
	MM CFG L00801	Nautical Blue Grease	125 ml
	MM CFG L00802		500 ml
	MM CFG L00803		1000 ml
	MM CFG L00804		5000 ml
	MM CFG L00900	24 Tubes Displayer	For 125 ml tubes



CLEANERS AND LUBRICANTS

	Code	Description	Size
	MM CFG C1101	Electronic Cleaner	200 ml
	MM CFG C1102		400 ml
	MM CFG C0704	Contacts Cleaner	150 ml
	MM CFG C0703		300 ml
	MM CFG C0801	Contacts Desoxidizer	200 ml
	MM CFG C0901	Contacts Lubricant	200 ml
	MM CFG C1001	Dust Free	200 ml
	MM CFG C0173	6-66 Multipurpose Anti-Corrosive	200 ml
	MM CFG C0172		400 ml
	MM CFG C0101	2-26 Electro	200 ml
	MM CFG C4501	Teflub Marine PTFE Dry Lubricant	400 ml



SILICONES

	Code	Description	Size
	MM CFG C1901	Silicone Spray	200 ml
	MM CFG C1801	Silicone Grease	200 ml



HIGH TEMPERATURE PAINTS



Code	Description	Size
MM CFG S0520	High Temp Paint WHITE	Aerosol 400 ml
MM CFG S0510	High Temp Paint ALUMINIUM	Aerosol 400 ml
MM CFG S0500	High Temp Paint BLACK	Aerosol 400 ml
MM CFG S0540	High Temp Paint RED	Aerosol 400 ml



HIGH TEMPERATURE SILICONES



Code	Description
MM CFG P00100	CFG 343°C Red Silicone Gasket
MM CFG P00200	CFG 260°C Black Silicone Gasket

HAND-CLEANING CREAM



Code	Description
MM CFG 00700	White. 3 LT Dispenser



WEST SYSTEM 205 EPOXY FAST HARDENER



205 Hardener is a medium-viscosity epoxy curing agent. It is used in a majority of situations, at lower temperatures and to produce a rapid cure that develops its physical properties quickly at room temperature.

Code	Size
MM WST 205/1KG	1 KG



WEST SYSTEM 206 EPOXY SLOW HARDENER



206 Slow Hardener is a low-viscosity epoxy curing agent for use when extended working and cure time is needed or to provide adequate working time at higher temperatures.

Code	Size
MM WST 206/1KG	1 KG



WEST SYSTEM 105 EPOXY RESIN



105 Resin is the base material of the WEST SYSTEM family of products, on which all of the WEST SYSTEM compounds are built. The resin is a clear, pale yellow, low-viscosity liquid epoxy resin. Formulated for use with WEST SYSTEM hardeners, it can be cured in a wide temperature range to form a high-strength solid with excellent moisture resistance.

Code	Size
MM WST 105/1KG	1 KG



PACKS



Code	Description
MM WST 104KIT	West System Junior Pack 105+205 (500+100gr)
MM WST 105205/1LT	West System 105-205 Epoxy Pack 1,2 Kg
MM WST 105206/1LT	West System 105-206 Epoxy Pack 1,2 Kg

LOCTITE
SPECIAL PRODUCTS

	Code	Description	Size
	MMLOC222	Thread Locking Low Strength	10ml/50ml/250ml
	MMLOC243	Thread Locking Medium Strength	10ml/50ml/250ml
	MMLOC272	Thread Locking High Strength	10ml/50ml/250ml
	MMLOC542	Thread Sealing Fine Thread	10ml/50ml/250ml
	MMLOC586	Thread Sealing Medium Thread	10ml/50ml/250ml

	Code	Description	Size
	MMLOC577	Thread Sealing Coarse Thread	50ml/250ml
	MMLOC573	Gasketing Rigid Metal Flange	250ml
	MMLOC5926	Gasketing Flexible Metal/Plastic Flange	40ml
	MMLOC401	Instant Bonding Low Viscosity	3g/20g/50g
	MMLOC431	Instant Bonding Medium Viscosity	20g
	MMLOC454	Instant Bonding Gel, non drip	10g/20g
	MMLOCATTACK	Super Attack Liquid Glue	5g

**Complete range of Loctite products
available upon request**

TEFLON


Code	Description
MM MANSU TEFLON	Teflon PTFE Roll 12 MM

WD 40


Code	Description
MM WD 40-250	WD-40 Oil Smartstraw 250 ml
MM WD 40-500	WD-40 Oil Smartstraw 500 ml

Notes